

METHOD, SERVER AND ARRANGEMENT IN A COMMUNICATION NETWORK

EL 525018071US

5 FIELD OF INVENTION

The present invention relates to an application level server, a method and an arrangement in a digital communication system. More specifically the present invention relates to resources reservation for establishing end-to-end quality of service.

10

DESCRIPTION OF RELATED ART

Multimedia communications has been explored in a number of different organisations and bodies. The currently predominant framework for multimedia in packet-based networks is provided by International Telecommunication Union –
15 Telecommunication sector (ITU-T) recommendation H.323 and its associated recommendations. H.323 describes an architecture for multimedia as well as a suite of protocols for its operation. Other schemes for multimedia communication also exist and may equally apply for the application, such as those developed by IETF in e.g. workgroups Multiparty Multimedia Session Control (MMUSIC) and
20 Session Initiation Protocol (SIP) with protocols such as SIP, Session Description Protocol (SDP) and Real Time Streaming Protocol (RTSP).

The packet network is commonly based on the Internet Protocol (IP). The IP network may or may not support the reservation of resources or any other
25 mechanism to provide quality of service. In the absence of real resource reservation mechanisms, the H.323 procedures of admission requests, bandwidth requests etc. are more of an authorisation nature and do not guarantee any service performance per se. In order to provide a reliable service with a predictable and guaranteed level of service and behaviour, Quality of service needs to be provided
30 by the underlying IP network so that resources can be allocated to cater for the application's needs.

When introducing multimedia communications in a cellular environment, the radio spectrum efficiency must be optimised due to the high costs involved. At the same time, and competing with the efficiency issue, a certain quality and service behaviour must be combined with a maintained multimedia service flexibility.

One method to provide an IP bearer quality of service is provided in the Integrated Service (IS) framework of Internet Engineering Task Force (IETF) and within IS using a Resource reSerVation Protocol (RSVP). IS with RSVP may be used to provide end-to-end Quality of service.

RSVP is a per flow, i.e. unidirectional, reservation protocol in which the source host of the flow initiates a reservation procedure by sending an RSVP Path (*Path*) message towards the flow sink host. It is then the task of the sink host to perform the actual reservation upstream towards the source host by returning an RSVP Reservation (*Resv*) message. The message includes information of desired bandwidth and other channel resources. The source host then confirms the reservation (*ResvConf*).

The application of RSVP in conjunction with H.323 multimedia is specified in the ITU-T H.323 02/98 standard. A schematic block diagram of one way of performing the basic operation of resource reservation H.323 capable environment is shown in **Figure 1**. A communication system 100 includes an H.323 Gatekeeper (GK) 101, which is a H.323 entity, that among other things can provide address translation, access control, and bandwidth management to the Local Area Network (LAN) for H.323 terminals and Gateways. Figure 1 is simplified and schematic, and call signalling, terminal capability exchange, master slave determination etc. are excluded in the Figure. Focus is on relevant parts of the signalling between a terminal 102, the H.323 Gatekeeper 101, an RSVP capable subnetwork 103, a H.323 capable IP network 104 and an end node 105.

The H.323 client 106 resides in the application layer, the RSVP 107 belongs more in the IP layer and in the Figure also the link layer is 108 shown. The layers referring to the Open Systems Interconnection (OSI) model, which is an international recommendation defined by International Standard Organisation (ISO). The example shown relates to a Gatekeeper routed call and H.245 control version. The ITU-T H.245, 09/98 standard is a control protocol for multimedia communication.

Below is a list of the significant steps carried out for resource reservation:

- 109 In the Admission ReQuest (ARQ) of H.323 the client indicates that it has a capability to reserve resources by setting the *TransportQoS* field value of ARQ appropriately.
- 110 The H.323 GK confirms the request by returning Admission Confirmed (ACF), and in this example indicating that the client may use its resource reservation capabilities.
- 111 When it is time, the client opens a logical channel by sending an *OpenLogicalChannel* message of H.245 to the gatekeeper including information regarding the requested quality of service in the *QoSCapability* field, which then contains the requested RSVP parameters.
- 112 The *OpenLogicalChannel* message is sent across the network usually to the other endpoint.
- 113 When step 112 has been acknowledged with an *OpenLogicalChannelAck* message, it is time to request the IP bearer service with the appropriate quality of service which is typically initiated by the H.323 client application which requests quality of service from the RSVP functional entity of the terminal 102, as indicated by step 113 in the Figure.
- 114 The initiation of the quality of service request is performed by sending the RSVP *Path* message to the subnetwork 103 and
- 115 further on to the end node 105 via the IP network 104.

A more complete signal flow for the above mentioned steps is shown in **Figure 2** where a bi-directional communication for a two-way speech is established. The *OpenLogicalChannel* is assumed here to establish a bi-directional logical channel. RSVP establishes one reservation per flow direction. In this fashion, resources are reserved within the IP layer and quality of service as required is provided. Note that the resource reservation is independent of the underlying link layer technology. This is a necessity in order to be able to provide quality of service end to end across heterogeneous networking technologies where IP is the common denominator.

The current multimedia solutions have been built with fixed access networks in mind. Care has not been taken to act for the specific needs of a cellular or wireless environment.

Figure 3 shows a schematic and simplified view of one example of an application of multimedia communication based on H.323 signalling 301 in a cellular environment. The terminal 302 could for instance comprise a cellular phone connected to a laptop running the H.323 client software. Other configurations are also possible. The terminal has, via a Radio Access Bearer 303 over the air interface access to a radio access node 304 which in turn has access to the rest of an H.323 capable IP network 305. The wording "radio access node" used in this patent application is a general wording and shall not be mixed up with the particular radio access nodes as they may be defined in other technologies e.g. in GSM, EDGE, UMTS etc. A Gatekeeper 306 and an end node 307 are connected to the network.

QoS is typically required end to end 308 including over the radio access. The terminal 302 has the capability to reserve resources using RSVP.

Using known art of resource reservation in combination with H.323, a typical sequence diagram of the resulting signalling between the Terminal 302, the Radio Access Node 304, the Gatekeeper 306 and the rest of the H.323 capable IP network 305 is provided in **Figure 4**. The signalling between the Terminal 302 and the Radio Access Node 304 is performed over the Air Interface 400. The signalling is extracted to show only the parts relevant to the actual resource reservation.

401 The terminal 302 requests admission to establish a call using H.225.0/RAS signalling, ITU-T H.225.0/RAS is protocol for Registration, Admission and Status signalling for packet-based multimedia communications systems. The terminal 302 also indicates that it has capabilities to reserve resources in the TransportQoS field in the ARQ message. The request is accepted and confirmed by the Gatekeeper 306 by returning ACF which notifies that the Terminal 302 may use its resource reservation capabilities.

402 Call control signalling (CCS) using H.225.0/Q.931 as well as other signalling such as master slave determination, terminal capability exchange etc. using H.245 signalling takes place. ITU-T H.225.0/Q.931 is protocol for Call Control signalling and ITU-T H.245 09/98 is a control protocol for multimedia communication.

403 A bi-directional logical channel is opened containing the resource reservation quality of service parameters in RSVP format using H.245 signalling.

404 A radio access bearer 303 is established with a corresponding quality of service. How this is done, when it is done etc. is of no significance here, only that it is necessary at some stage.

405 The resource reservation for an end to end quality of service IP bearer service is established using RSVP signalling. This is done using the previously exchanged quality of service parameters. The reservation is done per flow, in this case for a bi-directional communication.

It is obvious that the extensive signalling presents both a performance and cost problem over the air interface. The signalling is required for establishing the quality of service but also for maintaining the quality of service since RSVP uses a so-called soft state mechanism in which the RSVP messages are periodically sent (typically 30 s. intervals) to refresh the bearer reservation. The typical messages of H.245 have a mere length of 20 bytes, whereas RSVP messages have typical lengths of 150 to 230 bytes.

SUMMARY OF THE INVENTION

The problems discussed in the present disclosure are the following.

In a cellular environment, radio spectrum efficiency is of paramount importance. The cost for radio spectrum is high, and it is a strong desire to utilise the radio spectrum for as many users as possible at any given instance in time. Therefore the need to conserve channel bandwidth is of very high interest. On the other hand, the end user expects a certain level of service quality, or service behaviour, of which service response time to an end-user service request is one, requiring low latency of signalling message transfer and small amount of signalling messages to be exchanged.

These two requirements represent a duality problem. Looking at control signalling, the resulting signalling load is dependent on the number of messages exchanged over the air, as well as the message lengths. By narrowing the control channel bandwidth, the message transfer time increases and the network response time perceived by the end user increases accordingly.

To sum up, the resource reservation signalling costs a significant amount of bandwidth. Therefore, in cases with bandwidth restrictions or high cost of

bandwidth, a method of establishing quality of service end-to-end, but without resource reservation signalling over the access bearer, is needed.

Another problem is when end-to-end IP quality of service is desirable but the terminal lacks a resource reservation protocol on IP level. In this case is also a method needed for establishing quality of service end-to-end, in which no IP resource reservation signalling takes place over the access bearer.

Accordingly, it is an object of the present invention to unravel the above-mentioned problems.

The solution, according to the invention is to remove the resource reservation protocol signalling on the IP level, over the access interface, e.g. the expensive and narrow radio channel, and introduce a resource reservation protocol proxy in the network. The introduction of the proxy functionality still supports the possibility, or meets the requirement, to reserve resources end to end by establishing resources with quality of service on the link layer over the access interface.

An application level server for managing the resource reservation to establish quality of service according to the invention includes a functional entity. This functional entity identifies necessary parameters required for performing the resource reservation and changing signalling messages. The functional entity further requests from a resource reservation protocol proxy, quality of service between an access node and an end node. The server instructs the terminal to not use its resource reservation protocol if it has any. A server according to this first aspect of the invention is hereby characterised by what is the features of claim 1.

A communication system for carrying out resource reservation to establish quality of service between a terminal and an end node includes an IP network. A resource reservation protocol proxy, the end node and the application level server mentioned above are connected to the IP network. The terminal is connected to

an access node by means of establishing an access bearer with quality of service in a link level. The access node is connected to the resource reservation protocol proxy which performs resource reservation to establish quality of service on an IP level, between the proxy and the end node. The IP network uses a resource reservation protocol. A communication system according to this second aspect of the invention is hereby characterised by what is the features of claim 15.

According to a third aspect of the invention, the server indicates that the resource reservation signalling applies from the access node towards the end node. The server further identifies parameters, necessary for reserving resources to establish quality of services. The proxy reserves resources with quality of service on the IP level, according to the necessary parameters. The resources are reserved between the access node and the end node. An access bearer with a quality of service on the link level is established between the terminal and the access node. A method according to this third aspect of the invention is hereby characterised by what are the features of claim 20.

According to a fourth aspect, the invention can be implemented by software code segments and e.g. be stored in any of the relevant entities of a communication system, such as a resource reservation proxy, an application level server, a gatekeeper etc. The computer program product is directly loadable into the internal memory of a digital computer within the entities and includes the software code portions for performing the steps of the method according to the invention, when said program is run on a computer. A computer program product according to this fourth aspect of the invention is hereby characterised by what are the features of claim 41.

According to a fifth aspect of the invention the computer program product is stored on a computer usable medium, comprising readable program for causing a computer, within an entity in the communication system according the invention, to control an execution of the steps of the method according to the invention. A

computer program product according to this fourth aspect of the invention is hereby characterised by what are the features of claim 42.

5 An advantage of the present invention is that less bandwidth is required over the terminal access interface since the resource reservation signalling is removed over the access interface.

10 Another advantage of the present invention is that it is possible to establish end-to-end quality of service even if the terminal has no capabilities to reserve resources at the IP level over the access interface.

15 A further advantage of the present invention is that it implies transparency for applications across the network. The end node sees no difference whether the terminal has used resource reservation or if the proxy has done it on behalf of the terminal instead. Also as the server has the possibility to decide whether the terminal shall use resource reservation or not, the introduction of the resource reservation protocol proxy has no impact on existing implementations of terminals.

20 The wording resource reservation protocol used in this patent application shall be interpreted as a general wording, including any protocol for reserving resources at IP level.

25 Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

Figures 1-4 relates to Prior Art and are thus described above under “Description
of related art”.

- Figure 1 is a block diagram showing the basic operation of resource reservation in an H.323 environment.
- Figure 2 shows a schematic signalling sequence over the basic operation of resource reservation using RSVP in the H.323 architecture.
- Figure 3 is a schematic block diagram illustrating a multimedia communication based on H.323 in a cellular environment.
- Figure 4 shows a schematic signalling sequence over the basic operation of applying the H.323 architecture in a cellular environment.
- Figure 5 shows a flowchart of the method according to the invention
- Figure 6 is a schematic block diagram illustrating a communication system according to the invention.
- Figure 7 is a block diagram showing the application level server according to the invention.
- Figure 8 shows a signalling sequence diagram according to the invention.

DESCRIPTION OF PREFERRED EMBODIMENTS

Figures 1-4 are Figures related to Prior Art and are described under “Description
of related art”.

When communicating over IP and requiring resource reservation e.g. for voice over IP, multimedia, real-time conversational services, audio streaming, video streaming, web surfing with a guaranteed bitrate, etc., etc., there is a requirement both of bandwidth efficiency and a necessary IP quality of service, needing a significant degree of expensive bandwidth, as identified above. Another problem

is when a terminal does not have the possibility to reserve the necessary IP quality of service, but quality of service is required.

The solution relies on the facts that the underlying link layer in the access interface, e.g. the radio interface, can provide the required quality of service over the link. This link is a dedicated resource, and it provides the necessary and required quality of service in a predictable and guaranteed way. Reserving the necessary link quality of service, such as bandwidth, means that resources at the IP layer need not be explicitly reserved over the access interface. In the access network, resource reservation protocol signalling can be generated and terminated using a resource reservation protocol proxy, thus fulfilling the requirement of an IP bearer quality of service end-to-end.

Figure 5 shows a flowchart of establishing end-to-end quality of service according to the invention in a general mode. The quality of service is established between a terminal and an end node over an IP network in a communication system. The communication system includes the IP network, using an resource reservation protocol, to which are connected:

- the terminal via an access node;
- the end node;
- an resource reservation protocol proxy; and
- an application level server that manages and maintains resource reservation, as depicted in Figure 7.

The network and the entities use a resource reservation protocol on IP level, but the terminal might not use any resource reservation protocol on IP level. An opportunity to use the invention is when the network want to use a resource reservation protocol but the terminal does not have any resource reservation protocol. Instead it might have Asynchronous Transfer Mode (ATM) on the link level on which IP packets are transported. The terminal might use an access bearer on ATM level between the terminal and the access node.

The resource reservation protocol proxy and the server include each a respectively digital computer having an internal memory for storing a computer program.

5 The method includes the following steps:

501 The server indicates that the resource reservation signalling applies from the access node and towards the end node;

10 502 The server identifies parameters necessary for the resource reservation to establish end-to-end quality of service;

503 The resource reservation with quality of service on the IP level, between the access node and the end node is performed by means of the resource reservation protocol proxy.

15 504 An access bearer is established, with a quality of service, between the terminal and the access node on the link level, e.g. on the ATM level or the radio link level;

It is also possible to perform step 504 before step 503 or simultaneously.

A more detailed description of the inventive method follows under Figure 8.

20 **Figure 6** shows a schematic view of a communication system 600 in which quality of service is established between a terminal 605 and an end node 608 according to the invention. The communication system 600 is based on H.323 communication 601 in a cellular environment, e.g. based on General Packet Radio Service (GPRS), Enhanced Data rates of GSM and TDMA/136 Evolution (EDGE), and UMTS
25 Terrestrial Radio Access Network (UTRAN) in Universal Mobile Telecommunication System (UMTS).

In this embodiment of the invention, the entities and the IP network uses the Resource Reservation Protocol (RSVP). Thus constitutes the resource reservation
30 protocol proxy of an RSVP proxy 602, which in this case resides in a radio access

node 603 within a subnetwork 604. The subnetwork in turn has access to an H.323 capable IP network 607.

The RSVP proxy 602 has means 613 for performing resource reservation to establish quality of service on an IP level, between the access node and the end node.

The terminal 605 and the access node 603 has both means 612 for establishing a radio access bearer with a quality of service on the link layer between terminal 605 and the access node 603.

The RSVP proxy 602 might reside in other entities in the subnetwork 604, which entities are not depicted in Figure 6, where it is situated is not significant for the invention.

The subnet might e.g. constitute a radio access network or a radio access network and a core network.

The scenario applies to a H.323 Gatekeeper routed call scenario. The terminal 605 might consist of a laptop running the H.323 client software connected to a radio modem, providing the radio access. Other configurations are also possible.

The terminal 605 has access to the radio access node 603 via a radio access bearer 606. The end node 608 is connected to the IP network 607.

The communication system includes an application level server 609 according to the invention, which is shown more in detail in **Figure 7**. The application level server 701 is connected to an IP network 702 and manages the resource reservation process of establishing quality of service, between a terminal 703 and an end node 704 by means of an resource reservation protocol proxy 705 according to the invention. The terminal 703 is connected to the IP network 702 via an access node 706, the access node 706 is connected to the proxy 705 and the proxy 705 is connected to the IP network. The end node 704 is connected to the IP network 702, which IP network 702 uses a resource reservation protocol. The server 701 might be e.g. a Gatekeeper managing H.225 and H.245 signalling protocols or a SIP proxy managing SIP, according to Prior Art, which according

to the invention is modified to include a functional entity 707 that manages the resource reservation process of establishing quality of service by means of the resource reservation protocol proxy 705.

5 The server 701 has means 712 for indicating that the resource reservation protocol signalling applies between the proxy 705 the end node 704. Various means exists to accomplish quality of service between the proxy 705 and the access node 706, e.g. using over provisioning.

10 The functional entity 707 in the server has means 708 for identifying necessary parameters, from e.g. signalling messages, to be used for performing the resource reservation process.

Examples of necessary parameters are the receiver IP address of the end node 704, the receiver port identity of the end node 704, which quality of service mode 15 the end node 704 intends to use and possibly quality of service information such as required bandwidth. The latter might be found out by the server by knowledge of the application e.g. the server notes that Global Service for Mobile transmission (GSM) speech encoding is used by the application and it and knows 20 that the specific speech codec to be used in GSM, requires a specific amount of bandwidth. (A port is used in IP based systems to further address the process in the host to which the IP packet shall be forwarded.)

The functional entity 707 in server 701 also has means 709 for instructing the terminal to not use its resource reservation protocol if it has any.

25

The functional entity 707 in server 701 further has means 710 for changing signalling messages between the terminal 703 and the end node 704 and possibly other gatekeepers.

The terminal that is instructed to not use its resource reservation protocol 30 indicates, in a signalling message towards the end node 704, that it has no resource reservation capabilities, but the end node 704 that has to use the resource

reservation protocol towards the access node, has to get the information that there are resource reservation capabilities.

The terminal also indicates in another signalling message towards the end node that it **shall not use** resource reservation capabilities, but the end node 704 that shall use the resource reservation protocol towards the access node, has to get the information that resource reservation capabilities shall be used.

Signalling messages like these, passing the server 701 on its way towards the end node 704 or the terminal 703, are accordingly changed by the functional entity 706, before they are forwarded.

The functional entity 707 in server 701 also has means 711 for requesting from the resource reservation protocol proxy 705 the required quality of service between the proxy 705 and towards the end node. The by the functional entity 706 aggregated necessary parameters are passed on to the resource reservation protocol proxy 705. The resource reservation protocol proxy then performs the resource reservation with the requested quality of service between the proxy 705 and the end node 704.

Back to **Figure 6**. The server 609, which is also connected to the IP network 607, constitutes, in this example of the present invention, a H.323 Gatekeeper 609 modified to including means 610 for managing the process of using the RSVP proxy 602 for establishing quality of service, as described above, under Figure 7.

The RSVP proxy 602 has means for performing resource reservation with a by the Gatekeeper 609 requested quality of service between the access node and the end node.

The “real” RSVP capable quality of service is in this example of the present invention provided between the radio access node 603 and the end node 608, but relying on the fact that the radio link 606 provides its guaranteed quality of service, a “virtual” quality of service 611 at the IP layer is provided end-to-end. The RSVP

proxy 602 and the GK 609 include each a respectively digital computer having an internal memory for storing a computer program.

Figure 8 shows schematically a sequence diagram of the phases of establishing end-to-end quality of service, according to the invention, in the scenario described in Figure 6. The entities and network described are the terminal 605, the Air interface 800 the radio access node 603 which includes the in Figure 6 depicted RSVP proxy 602, the Gatekeeper 609, the H.323 and RSVP capable IP network 607 and the end node 608.

This Figure is simplified and schematic to. Focus is on parts of the signalling, relevant to the inventive method.

801 The terminal 605 requests admission to establish a call using H.225/RAS signalling from the Gatekeeper 609. Since it in this case is an entity running RSVP it also indicates that it has capabilities to reserve resources in the *TransportQoS* field of the *ARQ* message. The request is accepted and confirmed by the Gatekeeper 609 which tells the terminal 605, that the terminal shall not use its resource reservation capabilities or alternatively that the Gatekeeper 609 will reserve the necessary resources, in the *TransportQoS* field of the *ACF* message.

802 Call control signalling CCS, using H.225.0/Q.931 takes place as well as other signalling such as master slave determination, terminal capability exchange etc. using H.245 signalling. Among these the capability exchange signalling, which is of significance for the present invention, is shown in Figure 8 as reference number 802. In the capability exchange signalling, the terminal 605 indicates in the *TerminalCapabilitySet* message, which is to be sent towards the end node 608, that quality of service not is going to be used since the terminal 605 is told to not use its resource reservation capabilities. But the end node 608 must not know the decision to not use resource reservation, since the quality of service will be established by the RSVP proxy within the radio access node 603. Accordingly, the Gatekeeper 609 changes the *QoSMode* field in the *TerminalCapabilitySet* message from

being **not** set to be **set**, as to indicate that quality of service is supported and also which type of quality of service mode, before it is forwarded towards the end node 608. This means that that RSVP signalling may be used between the radio access node 603 and the end node 607. The end node 608 answers, in a *TerminalCapabilitySet* message in the opposite direction, which quality of service mode it will use. In RSVP there are different classes of quality of service modes, e.g. guaranteed quality of service or controlled lode. When this message, on the way towards the terminal 605, passes through the Gatekeeper 609, the Gatekeeper 609 intercepts the quality of service mode and removes which quality of service mode to be used from the message before forwarding it. The quality of service mode is one of the necessary parameters, to be used for performing the resource reservation process as described under Figure 5. Further, this message indicates that quality of service is might be used, but the terminal 605 must not know that, since it will be established by the RSVP proxy within the radio access node 603. Accordingly also this message is further changed by the Gatekeeper 609 as to indicate that quality of service shall not be used, before it is forwarded to the terminal 605.

803 When it is time to open a bi-directional logical channel, the terminal 605 sends an *OpenLogicalChannel* of H.245 to the Gatekeeper 609 which will forward the message further on to the end node 608. One bi-directional logical channel is opened for each type of flow needed, e.g. one for video, one for audio, one for data etc. Information conveyed may possibly contain the quality of service information, e.g. required bandwidth, type of delay, etc., (depending on the value returned by *TransportQoS* in the *ACF*). This quality of service information, such as peak bandwidth in bytes/sec, may be intercepted by the Gatekeeper 608 when it receives the *OpenLogicalChannel* message, but might also be deduced by the Gatekeeper 609, using knowledge about the application, e.g. if a channel with a GSM codec is opened, the GK 608 knows that it requires a specific amount of bandwidth etc. Other conveyed information is that receiver port

etc. supplied is that of the RSVP proxy in the radio access node 603 and not the port within the terminal 605. Further conveyed information of significance is where, in the end node 608, the logical channel shall terminate, e.g. by indicating the port identification of the port to be used.

5 This is returned in the *OpenLogicalChannelAck* message by the end node 608 to the terminal 605 via the Gatekeeper 609. The terminal receiver port identity etc. is used in the subsequent RSVP *Path* message received from end node 608.

804 The Gatekeeper 609 requests quality of service from the RSVP proxy in the radio access node 603, in a request quality of service message. The quality of service is requested between the radio access node 603 and the end node 608. The Gatekeeper 609 includes, the obtained quality of service information, quality of service mode, the receiver port identity of the end node 608 in the message to the RSVP proxy.

15 805 To establish a reservation between the RSVP proxy 602 in the radio access node 603 and towards the end node 608 to be used for a media stream going in the direction from the terminal 605 towards the end node 608, the RSVP proxy 602 in the radio access node 603 initiates the necessary resource reservation towards the end node 608, as requested in step 704, using the RSVP signaling message *Path* (as if it were sent from the terminal). The message includes the obtained quality of service information, quality of service mode and the receiver port identity of the end node 608, which are necessary for performing the resource reservation.

20 When the subsequent RSVP *Resv* message is returned from the end node 608 towards the terminal 605, it is intercepted by the RSVP Proxy 602 which does not pass it on to the terminal 605. As a response to the *Resv* message, the RSVP Proxy 602 generates and sends an RSVP *ResvConf* message towards the end point 608 (as if it were sent from the terminal).

25 To establish a reservation between the RSVP proxy 603 and towards the end node 608 to be used for a media stream going in the direction from the end node 608 and towards the terminal 605, the end node 608 (or

30

another entity acting on behalf of the end node, such as the inventive proxy) initiates the necessary resource reservation towards the terminal 605 by sending an RSVP *Path* message towards the terminal 605. The *Path* message contains the necessary quality of service information, quality of service mode and the receiver port identity of the terminal 605, which are necessary for performing the resource reservation. The *Path* message is then intercepted by the RSVP proxy 602 in the radio access node 603 and is not passed on to the terminal 605. The RSVP Proxy 602 responds to the *Path* message by returning an RSVP *Resv* message toward the end point 608 (as if it were sent from the terminal). When the confirmation of the resource reservation is received in the RSVP *ResvConf* message from the end node 608 (or an entity acting on behalf of the end node, such as the inventive RSVP proxy) it is intercepted by the RSVP proxy 602 and not passed on to the terminal 605. The reservation is done per flow, in this case for a bi-directional communication.

A radio access bearer is established with a corresponding quality of service between the link layer in the terminal 604 and the link layer in the radio access node 603. In a UMTS network scenario, this would be initiated by the terminal 605 sending an *ActivatePDPContextRequest* message according to UMTS Session Management signaling (Technical Specification 24.008: "Mobile Radio Interface layer 3 specification, core network protocols – stage 3", v3.2.1, 3rd Generation Partnership Project (3GPP)). When it is done is of no significance for the invention, only that it is necessary at some stage.

The end result is that resources are guaranteed end-to-end, but without sending RSVP over the air interface.

The methods according to the invention described are respectively implemented by means of a computer program product comprising the software code portions

for performing the steps of the method. The computer program product is run on a computer stored in a digital computer within the server and within the resource reservation protocol proxy.

The computer program is loaded directly or from a computer usable medium,
5 such as a floppy disc, CD, Internet, etc.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000